

DURiTE ECO

BOX3 Edge 1.5W



FEATURES

- Ensures excellent brightness and uniform lighting
- Suitable for minimum 3" depth cabinet signs
- Recommend 0.65ft ~ 4ft for double sides / 0.65ft ~ 1.6ft for single side
- Specially designed durable lens that withstands harsh environment and protects the LED
- Easy installation with double sided 3M tape and screw holes
- IP65 Waterproof and approved by UL, CE, RoHS
- Long life time 50,000 hours

DESCRIPTION

DURiTE ECO Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable LED that makes high performance and durability as Tier 1 LED.


Starux's most cost-efficient model and easy installation with double sided 3M tape.

Designed durable cover that withstands harsh environment and protects the LED.

SPECIFICATIONS

Model	BOX3 Edge 1.5W	Module Spacing	2 pcs/ft
Colors	6800K	Demension	2.5" x 0.9" x 0.38"
Lumens	135 lm/Mod	Weight	15g
Power	1.5W	Max in series	20 Mods
Input Voltage	12V DC	Operating Temp.	-4°F ~ 122°F / -20°C ~ 50°C
CRI	>80 Ra	Life Time	40,000
Beam Angle	20° x 30°	IP Rating	IP65 Waterproof

DIMENSION



SAMPLE TEST

FABERIC	FABERIC METHOD	Lighting Distance (m)	Light Box Depth H (cm)	Illumination (LUX)	Density pcs x m	Power W/m ²
White sofe film	2 Sides	0.6	10	1553-1684	12 x 2	60
		0.8	10	1431-1165	12 x 2	45
		1	10	886-1252	12 x 2	36