

# DURiTE ECO

## MINI3 0.48W



## FEATURES

- Versatile wide angle lens with compact design
- Ensures excellent transmittance and uniform lighting
- 150 degree angle lens that spreads light evenly for no hot spots
- Specially designed durable cover that withstands harsh environment and protects the LED
- High luminous efficacy guaranteed up to 83 lm/W
- Easy installation with double sided 3M tape
- IP68 Waterproof and approved by UL, CE, RoHS
- Long life time 50,000 hours

## DESCRIPTION

DURiTE ECO Series is Specialized for Channel Letter Signs.

The LED is powered by Reliable LED that makes high performance and durability as Tier 1 LED.


Starux's most cost-efficient model and easy installation with double sided 3M tape.

The ultrasonic welding technology performs for excellent waterproofing and protects LED from harsh environment.

## SPECIFICATIONS

<b>Model</b>	MINI3 0.48W			<b>Module Spacing</b>	4 pcs/ft
<b>Colors</b>	3000K	6500K	10000K	<b>Demension</b>	1.04" x 0.35" x 0.32"
<b>Lumens</b>	40 lm/Mod	40 lm/Mod	40 lm/Mod	<b>Weight</b>	2.5g
<b>Power</b>	0.48W			<b>Max in series</b>	50 Mods
<b>Input Voltage</b>	12V DC			<b>Operating Temp.</b>	-4°F ~ 122°F / -20°C ~ 50°C
<b>CRI</b>	>80 Ra			<b>Life Time</b>	50,000
<b>Beam Angle</b>	150°			<b>IP Rating</b>	IP68 Waterproof

## DIMENSION



## COVERAGE CHART

<b>Depth</b>	3"	4"	5"
<b>Max Stroke Single Row</b>	6"	8"	10"
<b>Max Stroke Multi Rows</b>	6"	8"	10"
<b>Mods per ft</b>	4 pcs per ft		

Parameters can be adjusted according to the desired brightness.